

WHAT IS CLAIMED IS:

1. A cathode ray tube apparatus comprising:

an electron gun assembly having an electron beam  
generating section which generates a plurality of  
5 electron beams and a main lens section which focuses  
the electron beams generated from the electron beam  
generating section on a phosphor screen; and

a deflection yoke which produces a deflection  
magnetic field that deflects the electron beams emitted  
10 from the electron gun assembly in a horizontal  
direction and a vertical direction,

wherein the main lens section comprises a focus  
electrode supplied with a focus voltage of a first  
level, at least one intermediate electrode supplied  
15 with a voltage of a second level equal to or higher  
than the first level, and an anode supplied with an  
anode voltage of a third level higher than the second  
level, the focus electrode, said at least one  
intermediate electrode and the anode being arranged in  
20 a direction of travel of the electron beams, and

the main lens section includes an electric field  
lens acting commonly on the electron beams on a focus  
region side of the main lens section, which is formed  
by the focus electrode and said at least one  
25 intermediate electrode, and a plurality of electric  
field lenses acting respectively on the electron beams  
on a divergence region side of the main lens section,

5

10

15

20

25

7. A cathode ray tube apparatus according to

claim 1, wherein said main lens section comprises a focus electrode, a first intermediate electrode, a second intermediate electrode and an anode, which are arranged in a direction of travel of the electron beams, and

the electric field lens acting commonly on the electron beams is formed by the focus electrode and the first intermediate electrode, and said plurality of electric field lenses acting respectively on the electron beams are formed by the second intermediate electrode and the anode.

8. A cathode ray tube apparatus according to claim 1, wherein said at least one intermediate electrode is connected to a resistor disposed near the electron gun assembly and supplied with a voltage obtained by resistor-dividing the anode voltage applied to the anode.

9. A cathode ray tube apparatus according to claim 1, wherein said focus electrode has a first focus electrode supplied with a reference voltage, and a second focus electrode supplied with a dynamic focus voltage obtained by superimposing upon the reference voltage an AC component varying in synchronism with the deflection magnetic field.

10. A cathode ray tube apparatus according to claim 9, wherein said second focus electrode and the intermediate electrode disposed adjacent to the second

focus electrode have, at their mutually opposing faces, outer peripheral electrodes defining opening portions which commonly pass the electron beams.

11. A cathode ray tube apparatus comprising:

5 an electron gun assembly having an electron beam generating section which generates a plurality of electron beams and a main lens section which focuses the electron beams generated from the electron beam generating section on a phosphor screen; and

10 a deflection yoke which produces a deflection magnetic field that deflects the electron beams emitted from the electron gun assembly in a horizontal direction and a vertical direction,

15 wherein the main lens section comprises a focus electrode supplied with a focus voltage of a first level, at least one intermediate electrode supplied with a voltage of a second level equal to or higher than the first level, and an anode supplied with an anode voltage of a third level higher than the second level, the focus electrode, said at least one  
20 intermediate electrode and the anode being arranged in a direction of travel of the electron beams,

25 said focus electrode has, in a face thereof opposed to the intermediate electrode disposed adjacent to the focus electrode, an electron beam passage hole which commonly passes the electron beams, and

said anode has, in a face thereof opposed to the

09995506.12001  
FOEET. 9095550

intermediate electrode disposed adjacent to the anode,  
a plurality of electron beam passage holes which  
individually pass the electron beams.

12. A cathode ray tube apparatus according to  
5 claim 11, wherein said intermediate electrode opposed  
to the focus electrode has, in a face thereof opposed  
to the focus electrode, an electron beam passage hole  
which commonly passes the electron beams, and

said intermediate electrode opposed to the anode  
10 has, in a face thereof opposed to the anode, a  
plurality of electron beam passage holes which  
individually pass the electron beams.

13. A cathode ray tube apparatus according to claim 11, wherein the focus voltage applied to the focus electrode is obtained by superimposing upon a reference voltage an AC component varying in synchronism with the deflection magnetic field.

14. A cathode ray tube apparatus according to claim 11, wherein the focus electrode includes an end face located on the side of the intermediate electrode disposed adjacent to the focus electrode and having a plurality of electron beam passage holes which individually pass the electron beams, and an outer peripheral electrode extending from said end face toward the intermediate electrode disposed adjacent to the focus electrode and forming an electron beam passage hole which commonly passes the electron beams.